



Peace Of Mind At Your Finger Tips

Manage All Your Security Devices From The One Location

Video Intercom

- Answer calls-Live view & two way audio
- Release electronic door (electric lock required)
- View CCTV cameras from indoor station
- Arm/Disarm alarm system & "Acusense Live-Guard" Solution" from Android indoor station



AX Pro Wireless Alarm

- Arm/Disarm alarm system
- Receive alarms with video verification
- Check device status



CCTV

- Live view, search and playback
- Save snapshots & record video "on the fly"
- Live view and record the intercom door station camera



Upgrade

"Warning! This is restricted area."


Acusense Live-Guard Solution

- Arm/Disarm live guard cameras
- Active deterrence with flashing LED & audible alert
- Two way audio via the built-in speaker and microphone
- Smart detection-human/vehicle classification
- Receive alarms with video verification
- Synchronize arm/disarm status from alarm system



Hik-(Connect

- Manage all of your devices from a single easy to use APP
- Share access with your family, friends or colleagues
- Download the APP via appstore.hikvision.com for IOS or Android OS devices





Recommended Products-CCTV



AcuSense

DS-2CD2386G2-ISU/SL

AcuSense Live Guard Camera

- 8 MP resolution
- · Target classification
- Active strobe light and audio alarm to warn intruders off
- 120dB WDR
- Two-way audio with built-in mic and speaker



ColorVu

DS-2CD2347G2-LU

ColorVu Camera

- 1/1.8' 4MP sensor with F1.0 advanced lenses
- 24/7 vivid colorful imaging
- Target classification
- 130dB WDR
- Built-in microphone







DS-2CD2387G2-LSU/SL

ColorVu Live Guard Camera

- 1/1.2' 8MP sensor with F1.0 aperture
- 24/7 vivid colorful imaging
- Target classification technology
- 130dB WDR
- Two-way audio with built-in mic and speaker



DS-7608NI-I2/8P

I Series NVR

- 8-ch IP input with PoE , plug&play
- 4*4K simultaneously decoding
- Acusense Live-Guard functionality

Recommended Products-Wireless Alarm



DS-PWA96-Kit-WB

AX PRO Wireless Alarm Kit

- Hub*1,keyfob*1,PIR*1,Magnetic contact*1
- · 96 Zones, 48 users,
- TCP/IP, Wi-Fi, and 3/4G network



DS-PS1-I-WB

Wireless Internal Sounder

- Up to 900 m transmission distance
- Up to 110 dB sounder output



DS-PDPC12PF-EG2-WB

Wireless PIR Camera

- Up to 800 m transmission distance
- Detection range: 12m/85.9°
- 24/7 colorful imaging
- · Up to 20 photos fused into a GIF



DS-PS1-E-WB

Wireless External Sounder

- Up to 900 m transmission distance
- Up to 110 dB sounder output
- IP 65
- 4 CR123A/12 VDC



DS-PK1-E-WB

Wireless Keypad

- Up to 900 m transmission distance
- Stay arming, away arming, disarming, and output control
- One-Push fire alarm, panic alarm, and medical alarm. Silent/Audible alarm selectable.



DS-PM1-I16O2-WB

Multi IO Transmitter

- Up to 800 m transmission distance
- 16 onboard inputs and 2 outputs, applied to connect wired detectors
- Two 12V power outputs to power up external wired detectors
- Large space for back up storage battery

Recommended Products-Intercom & Access Control



IP intercom

DS-KD8003-IME1

IP Modular Door Station

- Modular design, expansion-ready with various modules
- 2MP HD Fisheye Camera
- Standard PoE
- IP65



DS-KV8113-WME1(B)

Villa Door Station

- · 2MP HD Camera
- · Built-in Card reader
- Standard PoE
- IP65, IK08



DS-KH6320-WTE2

Indoor Station

- 7-Inch touch screen
- Wi-Fi 802.11b/g/n
- Remote access via Hik-connect



DS-KH9510-WTE1

Android Indoor Station

- 10.1-inch touch screen
- Built-in Hik-Connect App
- Control Centre for intruder alarm, CCTV and intercom systems
- Wi-Fi 802.11b/g/n
- Standard PoE

Two Wire IP intercom



DS-KH6320-WTE2

Indoor Station

- 7-Inch touch screen
- Wi-Fi 802.11b/g/n
- · Remote access via Hik-connect
- Standard PoE



DS-KAD706-P

Two Wire IP Distributor

- 6x2-wire cascade interfaces with device power supply
- Din rail mounting,24VDC



DS-KD8003-IME2

Two Wire Modular Door Station

- Modular design, expansion-ready with various modules
- 2MP HD Fisheye Camera
- IP65

Face recognition terminal



DS-K1T341AM

Face Recognition Terminal

- 4.3-inch LCD touch screen
- 3000 faces capacity
- Accuracy rate ≥ 99%;
- APP control: live view, receive call notification and unlock doors
- Compatible with HIK indoor stations
- IP65



DS-K2M060

Secure Module

- Access Point Secure Module
- RS-485 interface
- DC12V



- Tri-X and Cam-X wireless technology (Up to 1,200m)
- Real time feed via PIR CAM or IP cameras
- LAN/WIFI/3/4G
- SMS & VOICE call
- APP programming
- Support up to 210 multi-type wireless peripheral devices



- Upgraded CCTV system with arming/disarming function
- 4-in-1 camera-video, AcuSense, strobe and siren
- Active deterrence with flashing LED & siren alerts to warn off intruders
- Real-time notifications on Hik-Connect APP
- AcuSense technology Human/Vehicle classification





Video Intercom

- Excellent image quality 2 MP fisheye camera, IR, WDR
- IP solution with standard PoE design, or 2-wire solution for re-usage of existing wiring
- Receive push notifications and enable 2-way audio on Hik-Connect
- Manage all HIK devices IP cameras, NVRs, intrusion alarm and more in the android indoor station

200

Software & Platform

- Intuitive UI provides smooth experience
- Connect your devices with guaranteed data security and cloud-based services
- Real-time access to devices via P2P technology
- Convenient permission sharing

HIK-CONNECT



Easy to use

Intuitive UI provides smooth experience.

Adding devices by scanning the QR code. P2P connection. No port mapping is required.



Real-time notification

Receives real-time alarm notifications from devices.



Device sharing

Easy to share your devices with your family members, employees at the same time with limited permissions (playback, alarm notification, intercom, PTZ).



Secure

All data and transmission is encrypted.



One APP for all

 $\label{lem:compatible} \mbox{Compatible with Hikvision CCTV, Intercom, alarm, etc.}$

Supports live view/playback/intercom/remote entry control/arming and disarming control.

Recommended Applications -----











